





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : E21B 47/12		A1	(11) International Publication Number: WO 00/65198
(21) International Application Number: PCT/GB00/01629		(43) International Publication Date: 2 November 2000 (02.11.00)	
(22) International Filing Date: 27 April 2000 (27.04.00)			
(30) Priority Data: 60/131,208 27 April 1999 (27.04.99) US 9926545.6 9 November 1999 (09.11.99) GB		(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(71)(72) Applicant and Inventor: MCLOUGHLIN, Stephen, John [GB/GB]; 36 Wychwood Close, Bognor Regis, West Sussex PO21 4DW (GB).		Published With international search report.	
(74) Agent: GRANLEESE, Rhian, Jane; Marks & Clerk, 57-60 Lincoln's Inn Fields, London WC2A 3LS (GB).			

(54) Title: APPARATUS AND METHOD FOR TRANSMITTING INFORMATION TO AND COMMUNICATING WITH A DOWN-HOLE DEVICE



(57) Abstract

An apparatus for use in drilling or producing from a well bore, the apparatus comprising a downhole member such as a drilling device or a production device which is capable of being attached to a tubular such as a drill string, production string or the like, means for rotating a tubular, control means for controlling the rotation of said tubular in order to transmit information along said tubular and means for monitoring the rotation of said tubular and for decoding said information transmitted along said tubular such that a magnitude of a parameter can be determined by the drilling member from the rotation of said tubular. The invention also relates to a method for communicating with a downhole tool using the apparatus.